Table 2 - Estimated Savings for Gas-fired Water Heaters Using Softened Water Over 15 Years Life

| Cost Elements | Water Hardness (grains per gallon) | | | | | | |
|--|------------------------------------|----------|----------|------|------|------|------|
| | 0 | 5 | 10 | 15 | 20 | 25 | 30 |
| Instanta | meous (| Gas Wate | r Heater | s | | | |
| Percent Life Cycle Energy Cost Savings, %1 | NA | 5.4 | 5.4 | 5.4 | 5.4 | 5.4 | 5.4 |
| Percent Total Life Cycle Cost Savings, %1 | NA | 14.0 | 22.5 | 31.2 | 39.6 | 48.4 | 57.0 |
| Estimated Usage before Deliming Required, Years ² | NA | 8.4 | 4.1 | 2.7 | 2.0 | 1.6 | 1.4 |
| Gas | Storage | Water H | eaters | | | | |
| Life Cycle Operating Efficiency Reduction From Baseline, %3 | 0.0 | 4.3 | 8.5 | 12.8 | 17.0 | 21.3 | 25.5 |
| Percent Life Cycle Energy Cost Savings, %4 | NA | 3.1 | 6.6 | 10.3 | 14.5 | 19.0 | 24.2 |

² Derived from Table 5-1

³ Derived from Table 5-3

⁴ Derived from Table 5-4